



UHF TRUNKED RADIOS

IC-F620TR (25W)
IC-F621TR (45W)



Capture More of Your System's Range...and Profits

With more flexibility, more power, and more spectrum coverage the IC-F620/F621TR will allow you to load more customers on to your existing system. Combine this Icom trunking mobile with Icom's IC-F4TR portable and maximize your existing system's potential.

More Flexibility (3-in-1)

The IC-F620/F621TR offers basic LTR®, PassPort, and conventional operations in one unit. Conventional operation and talk around during trunking operation are both available with the touch of a button.

• LTR® Features and Select Call

Program up to 20 systems and up to 250 talk groups per system. All basic LTR® features, including DTMF direct calling with an optional DTMF microphone, HM-100TN, telephone interconnect and wide/narrow channel spacing are available.

• PassPort Features

The built-in receive signal strength indicator (RSSI) detects the strongest signal site, providing seamless roaming.

More Power (45W of Trunking Power*)

Maximize the footprint the FCC gave you. More power equals greater access/coverage. It also means more reliable handshakes at the edge of your footprint. (* IC-F621TR only.)

More Spectrum

Wide bandwidth of 440–490MHz with switchable 12.5/25kHz widths per channel allows for greater system configuration flexibility.

5 Prog. Buttons & Independent AF Volume Knob

P0–P4 buttons allow you to customize functions to meet specific needs. The independent volume knob provides quick operation.

Invertible Chassis for Clearer Speaker Audio

Whether installed under the dashboard or from the ceiling, point the speaker in the direction you need. The radio's chassis may be inverted to put the sound where you need it most.



Avoid installation and/or use of the radio in direct sunlight.

Icom Inc.

ADDITIONAL FEATURES

- CTCSS, DTCS encoder and decoder built-in
- Conventional, system and group scans
- Flash ROM CPU for firmware upgrade capability
- MIL810 rugged construction
- Advanced PC programming capability
- One touch abbreviated dialing with optional DTMF Microphone, HM-100TN
- Dead beat stuns the radio for certain periods

LTR is a registered trademark of the E.F.Johnson Company.
All other trademarks are the properties of their respective holders.

SPECIFICATIONS

- Frequency coverage : 400–430MHz, 440–490MHz
- Number of channels : Max. 250 channels (conventional)
- Power supply voltage : 13.6V DC
- Current drain (approx.) : Tx at 45W 13A
at 25W 7A
Rx max. audio 1.2A
standby 300mA
- Operating temperature range : -30°C to +60°C; -22°F to +140°F
- Antenna impedance : 50Ω (SO-239)
- Dimensions (W×H×D) : 140×40×170mm; 5½×19⅙×6⅛in
- Weight : 1.2kg; 2.6lb
- Rated output power : IC-F620TR 25W
IC-F621TR 45W
- Microphone impedance : 600Ω (8-pin modular)
- Audio output power : 4W typical at 10% distortion with a 4Ω load
- External speaker connector : 2-conductor 3.5 (d) mm (⅛"/4Ω)

Measurements made in accordance with EIA-152C/204D, TIA-603.
All stated specifications are subject to change without notice or obligation.

OPTIONS

- **HM-100N HAND MICROPHONE**
Same as supplied hand microphone.
- **HM-100TN DTMF MICROPHONE**
Hand microphone with a DTMF keypad.
- **OPC-617 ACC CABLE**
Connection cable for ignition SW, dimmer control, etc.
- **SM-25 DESKTOP MICROPHONE**
Convenient for dispatching. Equipped with monitor switch.
- **SP-10/SP-22 EXTERNAL SPEAKERS**
Input impedance: 4Ω; Max. input power: 5W



Compatible with IC-F4TR handheld

The IC-F620TR/F621TR is designed to be a companion to our handheld radio, IC-F4TR. Take advantage of the shared functionality to complete your communications requirements.

- Basic LTR®, PassPort and Conventional are built-in
- Simple and keypad version
- 8-digit LCD display
- MIL grade durability
- CTCSS, DTCS and DTMF encoder/decoder built-in



Applicable U.S. Military Specifications

Icom makes rugged products that meet MIL-STD requirements and strict environmental standards as follows.

Standard	MIL 810C		MIL 810D		MIL 810E		MIL 810F	
	Method	Proc.	Method	Proc.	Method	Proc.	Method	Proc.
Low Pressure	500.1	I	500.2	I, II	500.3	I, II	500.4	I, II
High Temp.	501.1	I	501.2	I, II	501.3	I, II	501.4	I, II
Low Temp.	502.1	I	502.2	I, II	502.3	I, II	502.4-3	I, II
Temp. Shock	503.1	I	503.2	I	503.3	I	503.4	I
Solar Radiation	505.1	I	505.2	I	505.3	I	505.4	I
Rain	506.1	I, II	506.2	I, II	506.3	I, II	506.4	I, II
Humidity	507.1	I, II	507.2	II, III	507.3	II, III	507.4	-
Salt Fog	509.1	I	509.2	I	509.3	I	509.4	-
Dust	510.1	I	510.2	I	510.3	I	510.4	I
Vibration	514.2	VIII, X	514.3	I	514.4	I	514.5	I
Shock	516.2	I, II, V	516.3	I, IV	516.4	I, IV	516.5	I, IV

Supplied Accessories

- Hand mic. (HM-100N)
- DC power cable
- Mounting bracket kit
- Fuses
- Key assign stickers

Icom Inc.

1-1-32, Kamiminami, Hirano-ku, Osaka 547-0003, Japan Phone: 06 6793 5302 Fax: 06 6793 0013 URL: <http://www.icom.co.jp/world/index.html>

Count on us!

Icom America Inc.

<Corporate Headquarters>
2380 116th Avenue N.E., Bellevue, WA 98004, U.S.A.
Phone: (425) 454-8155 Fax: (425) 454-1509
URL : <http://www.icomamerica.com>
<Customer Service> Phone : (425) 454-7619

Icom Canada

Glenwood Centre #150-6165 Highway 17,
Delta, B.C., V4K 5B8, Canada
Phone: (604) 952-4266 Fax: (604) 952-0090
URL : <http://www.icomcanada.com>

Icom (Australia) Pty. Ltd.

A.B.N. 88 006 092 575
290-294 Albert Street, Brunswick, Victoria, 3056, Australia
Phone: 03 9387 0666 Fax: 03 9387 0022
URL : <http://www.icom.net.au>

Icom New Zealand

146A Harris Road, East Tamaki, Auckland, New Zealand
Phone: 09 274 4062 Fax: 09 274 4078
URL : <http://www.icom.co.nz>

Icom (Europe) GmbH

Communication Equipment
Himmelgeister Str. 100, D-40225 Düsseldorf, Germany
Phone: 0211 346047 Fax: 0211 333639
URL : <http://www.icomeurope.com>

Icom Spain S.L.

Ctra. de Gracia a Manresa Km. 14,750
08190 Sant Cugat del Valles Barcelona, SPAIN
Phone: (93) 590 26 70 Fax: (93) 589 04 46
URL : <http://www.icomspain.com>

Icom (UK) Ltd.

Unit 9, Sea St., Herne Bay, Kent, CT6 8LD, U.K.
Phone: 01227 741741 Fax: 01227 741742
URL : <http://www.icomuk.co.uk>

Icom France S.a

Zac de la Plaine, 1, Rue Brindejonc des Moulinais
BP 5804, 31505 Toulouse Cedex, France
Phone: (33) 5 61 36 03 03 Fax: (33) 5 61 36 03 00
URL : <http://www.icom-france.com>

Asia Icom Inc.

6F No. 68, Sec. 1 Cheng-Teh Road,
Taipei, Taiwan, R.O.C.
Phone: (02) 2559 1899 Fax: (02) 2559 1874
URL : <http://www.asia-icom.com>

Beijing Icom Ltd.

1305, Wanshang Plaza, Shijingshan Road,
Beijing, China
Phone: (010) 6866 6337 Fax: (010) 6866 3553
URL : <http://www.bjicom.com>



Certificate Number Q14190

Icom Inc. (Japan), is an ISO9001 certification acquired company.

Your local distributor/dealer: